



**D Maschinenreibbahlen**  
mit Morsekegel,  
DIN 208 B

**Einsatzbereich:**  
Drallgenutete Ausführung mit 8° Linksspirale für alle E- und NE-Metalle geeignet.



**E Machine reamers**  
with morse taper shank,  
DIN 208 B

**Range of application:**  
For ferrous and non-ferrous metals. Slow helix type 8° left hand spiral.



**I Alesatori a macchina**  
cono morse,  
DIN 208 B

**Impiego:**  
Alesatori con taglienti elicoidali, elica sinistra ca. 8°.  
Adatti per tutti i materiali ferrosi, non ferrosi.

d1 <sub>H7</sub> mm	l1 mm	l2 mm	l3 mm		Z		Code 3130 Art.-Nr.
10,00	168	38	102,50	1	6	Ø 9,80 mm	0 3130010001 00
11,00	175	41	109,50	1	6	Ø 10,80 mm	0 3130011001 00
12,00	182	44	116,50	1	6	Ø 11,80 mm	0 3130012001 00
13,00	182	44	116,50	1	6	Ø 12,80 mm	0 3130013001 00
14,00	189	47	123,50	1	8	Ø 13,80 mm	0 3130014001 00
15,00	204	50	124,00	2	8	Ø 14,80 mm	0 3130015001 00
16,00	210	52	130,00	2	8	Ø 15,80 mm	0 3130016001 00
17,00	214	54	134,00	2	8	Ø 16,80 mm	0 3130017001 00
18,00	219	56	139,00	2	8	Ø 17,80 mm	0 3130018001 00
19,00	223	58	143,00	2	8	Ø 18,80 mm	0 3130019001 00
20,00	228	60	148,00	2	8	Ø 19,80 mm	0 3130020001 00
21,00	232	62	152,00	2	8	Ø 20,60 mm	0 3130021001 00
22,00	237	64	157,00	2	8	Ø 21,60 mm	0 3130022001 00
23,00	241	66	161,00	2	8	Ø 22,60 mm	0 3130023001 00
24,00	268	68	169,00	3	8	Ø 23,60 mm	0 3130024001 00
25,00	268	68	169,00	3	8	Ø 24,60 mm	0 3130025001 00
26,00	273	70	174,00	3	8	Ø 25,60 mm	0 3130026001 00
27,00	277	71	178,00	3	8	Ø 26,60 mm	0 3130027001 00
28,00	277	71	178,00	3	8	Ø 27,60 mm	0 3130028001 00
30,00	281	73	182,00	3	10	Ø 29,60 mm	0 3130030001 00



HSS-Reibbahlen  
HSS reamers  
HSS alesatori